

FEATURES:

- Drop forged hooks and hook holders, heat treated to ensure the safety and durability.
- Lightweight steel construction with durable powder coat finish.
- Sealed roller bearing adopted to increase efficiency and reliability.
- Non-slip rubber grip fastened to high strength handle lever.
- Free-wheeling mechanism for quick chain adjustments.
- High grade alloy steel G80 load chain adopted.



Model	Capacity (t)	Standard lift (m)	Running test load (T)	Load Chain G80		Effort required to lift max load (N)	Main Dimensions (mm)							Extra weight Per meter of extra lift (kg)	N.W (kg)
				Falls of Chain	Dia (mm)		A	B	C	D	K	H	L		
HSH-V0.75	0.75	1.5	1.125	1	6	145	155	60	135	40	24	300	255	0.8	7
HSH-V1	1	1.5	1.5	1	6	150	155	60	135	40	24	300	255	0.8	7
HSH-V1.5	1.5	1.5	2.25	1	7.1	200	165	65	145	44	31	365	365	1.1	10
HSH-V2	2	1.5	3	1	8	220	165	65	145	46	31	365	254	1.4	12
HSH-V3	3	1.5	4.5	1	10	280	185	85	195	50	34	440	365	2.2	18
HSH-V6	6	1.5	7.5	2	10	310	195	85	250	64	43	575	365	4.4	28.5
HSH-V9	9	1.5	11.25	3	10	320	195	85	335	85	55	700	365	6.6	45