

- # Adjustable steering handle for easy operation
- # Oil bath air filter to protect engine from its dusty and dirty work environment
- # Reverse lock-out design for safer operation
- # Axle system for easy operation
- # Protective front engine guard



Model	HZ-6210	HZ-6211
Rated Power	7.0/212 hp/cc	7.0/212 hp/cc
Starting Mode	Recoil Start	Recoil Start
Transmission Type	Belt + Chain	Belt + Chain
Gear Shifting	R,N,1,2	R,N,1,2
Tilling Width	920 mm	920 mm
Tilling Depth	≥100 mm	≥100 mm
Blade Type	4-3	4-3
Tyre Type	3.5-6	4.0-8
Packaging Dim	780 x 460 x 780 mm	780 x 460 x 780 mm
Weight	75 kg	87 kg

Mini Body

* Open mold for new gearbox, Air cool 20% better than normal, Surface smooth, Low noise, International corrosion level, Light weight & Design compact

Power Big

* Fully gear transmission, High efficiency, Long life span than belt type model will have 50% more power than belt model

Standard Accessories



Model	HZ-6220
Rated Power	7.0/212 hp/cc
Starting Mode	Manual Start
Transmission Type	Full Gear Transmission
Gear Shifting	2,1,0,-1
Rotary Width	1050 mm
Rotary Depth	>100 mm
Blade Type	4-3
Tyre Type	3.5-6 solid Rubber Wheel - 1 pair
Packaging Dim	880 x 460 x 660 mm
Weight	70 kg

- # Adjustable steering handle for easy operation
- # Oil bath air filter to protect engine from its dusty and dirty work environment
- # Reverse lock-out design for safer operation
- # Axle system for easy operation
- # Protective front engine guard
- # Direct coupled design that higher torque for harder soil
- # Quick adjust 3-position handle



Model	HZ-6221	HZ-6223
Rated Power	7.0/212 hp/cc	9.0/270 hp/cc
Starting Mode	Recoil Start	Recoil Start
Transmission Type	Gear	Gear
Gear Shifting	R,N,1,2	R,N,1,2
Tilling Width	1100 mm	1350 mm
Tilling Depth	≥100 mm	≥100 mm
Blade Type	4-4	5-4
Tyre Type	4.0-8 Rubber Wheel	4.0-8 Rubber Wheel
Packaging Dim	905 x 460 x 780 mm	910 x 570 x 780 mm
Weight	95 kg	121 kg

- # 360° design steering handle for easy operation
- # Oil bath air filter to protect engine from its dusty and dirty work environment
- # Multi-functional purpose
 - * Soil loosening
 - * Weeding
 - * Tilling



HZ-6350

Model	HZ-6350
Rated Power	7.0/212 hp/cc
Starting Mode	Recoil Start
Transmission Type	Belt + Gear
Gear Shifting	N,1,2
Tilling Width	600 mm
Tilling Depth	≥100 mm
Blade Type	3-3
Tyre Type	3.5-6
Packaging Dim	830 x 500 x 760 mm
Weight	58 kg

- * Shaft rotary direction, forward or reverse can changer by user
- * Miss plow (50mm)
- * Metal front wheel, adjust ditching depth
- * Heavy at front size, more easy to let tiller go inside coil, no need push
- * Fender design more profession
- * New design, hold handle can adjust handle turn left, up and down
- * Gearbox is cast iron, more strong



Model	HZ-6350E
Rated Power	7.0/212 hp/cc
Starting Mode	Manual Start
Transmission Type	Belt+Gear
Gear Shifting	Walk: 2,R,N,1 Work: 2,N,1
Tilling Width	700 mm
Tilling Depth	≥100 mm
Blade Type	3-4
Tyre Type	3.5-6 Rubber Solid Wheel
Packaging Dim	830 x 500 x 760 mm
Weight	63 kg

HZ-6310

HZ-6311



Model	HZ-6310	HZ-6311
Engine Type	1E44F-5, 2-Stroke	1E48F, 2-Stroke
Rated Power	1.7 kw / 52 cc	2.2 kw / 68 cc
Starting Mode	Recoil Start	Recoil Start
Transmission Type	Worm drive, Single gear	Double-geared drive
Tilling Width	250 mm	430 mm
Tilling Depth	100-150 mm	200-250 mm
Packaging Dim	460 x 450 x 300 mm	550 x 510 x 600 mm
Weight	20 kg	32 kg