



Harz earth augers are built to penetrate grounds quickly and are well suited to hard soils. They are ideal for taking soil samples & boring plant holes.



Model	HZ-6015	HZ-6020S
Engine	1E40F-5A	1E48F
Displacement	51.7 cc	63.3 cc
Power	1.25 kw / 6500 rpm	2.2 kw / 7500 rpm
Spindle Speed	160 rpm	183 rpm
Mixed Fuel Ratio	25:1 - 50:1	25:1 - 50:1
Reduction Ratio	40:1	40:1
Tank Capacity	0.98 L	1.45 L
Package Dimensions	550 x 335 x 395 mm	380 x 380 x 380 mm
Weight	9.8 kg	12 kg
Earth Auger Bit Length	800 mm	800 mm
Earth Auger Bit Diameter	100 / 150 / 200 mm	100 / 150 / 200 / 250 mm



Model	HZ-6021-52	HZ-6021-63
Engine	1E40F-5A	1E48F
Displacement	51.7 cc	63.3 cc
Power	1.25 kw / 6500 rpm	2.2 kw / 7500 rpm
Spindle Speed	160 rpm	183 rpm
Mixed Fuel Ratio	25:1 - 50:1	25:1 - 50:1
Reduction Ratio	40:1	40:1
Tank Capacity	0.98 L	1.45 L
Package Dimensions	930 x 520 x 360 mm	930 x 520 x 360 mm
Weight	23 kg	24 kg
Earth Auger Bit Length	800 mm	800 mm
Earth Auger Bit Diameter	100 ~ 200 mm	100 ~ 300 mm

OPTIONAL ACCESSORIES

Earth Auger Bit



Length
800mm
Diameter
100mm (4 Inch)
150mm (6 Inch)
200mm (8 Inch)
250mm (10 Inch)
300mm (12 Inch)

Extension



50cm

30cm

Spring





Model	HZ-1450
Displacement	25.4 cm³
Net weight	5.5 kg
Fuel tank capacity	0.7 L
Max power	0.7 kw / 7500 r/min
Drill chuck (American system)	2-13 mm / 2-20 UNF
Drill diameter	13/28 mm
Drill length	290/330
Reduction ration	Forward 19.58:1, Reverse 20.38:1