



IMPACT DRIVER



SI-1052

Shank Size: 1/4"
Max. Torque: 70 Nm
Bolt Cap: 5 mm
Free Speed: 13,000 rpm
Weight: 0.56 kg
Avg. Air Consumption: 2.3 cfm
Air Inlet: 1/4"



SI-1062

Shank Size: 1/4"
Max. Torque: 95 Nm
Bolt Cap: 6 mm
Free Speed: 11,000 rpm
Weight: 0.79 kg
Avg. Air Consumption: 2.8 cfm
Air Inlet: 1/4"



SI-1065

Shank Size: 1/4"
Max. Torque: 65 Nm
Bolt Cap: 6 mm
Free Speed: 11,000 rpm
Weight: 0.98 kg
Avg. Air Consumption: 3.4 cfm
Air Inlet: 1/4"



SI-1356D

Shank Size: 1/4"
Max. Torque: 55 Nm
Bolt Cap: 8 mm
Free Speed: 9,000 rpm
Weight: 1.22 kg
Avg. Air Consumption: 2.7 cfm
Air Inlet: 1/4"

SCREW DRIVER



SI-1161

Shank Size: 1/4"
Max. Torque: 5 Nm
Bolt Cap: 6 mm
Free Speed: 1,600 rpm
Weight: 1.12 kg
Avg. Air Consumption: 2.8 cfm
Air Inlet: 1/4"



SI-1166A

Shank Size: 1/4"
Max. Torque: 5 Nm
Bolt Cap: 6 mm
Free Speed: 2,000 rpm
Weight: 1.18 kg
Avg. Air Consumption: 3.5 cfm
Air Inlet: 1/4"



SI-1166-8A

Shank Size: 1/4"
Max. Torque: 9 Nm
Bolt Cap: 8 mm
Free Speed: 800 rpm
Weight: 1.35 kg
Avg. Air Consumption: 3.3 cfm
Air Inlet: 1/4"



SI-1370D

Shank Size: 1/4"
Max. Torque: 80 Nm
Bolt Cap: 8 mm
Free Speed: 9,000 rpm
Weight: 1.21 kg
Avg. Air Consumption: 4.3 cfm
Air Inlet: 1/4"

IMPACT WRENCH



SI-1355

Shank Size: 3/8"
Max. Torque: 90 Nm
Bolt Cap: 10 mm
Free Speed: 9,000 rpm
Weight: 1.12 kg
Avg. Air Consumption: 2.7 cfm
Air Inlet: 1/4"



SI-1420T

Shank Size: 1/2"
Max. Torque: 500 Nm
Bolt Cap: 16 mm
Free Speed: 6,000 rpm
Weight: 2.55 kg
Avg. Air Consumption: 4.0 cfm
Air Inlet: 1/4"

RATCHET WRENCH



SI-1320A

Shank Size: 3/8"
Max. Torque: 80 Nm
Bolt Cap: 12 mm
Free Speed: 160 rpm
Weight: 1.16 kg
Avg. Air Consumption: 2.7 cfm
Air Inlet: 1/4"



SI-1325A

Shank Size: 1/2"
Max. Torque: 90 Nm
Bolt Cap: 16 mm
Free Speed: 160 rpm
Weight: 1.17 kg
Avg. Air Consumption: 2.5 cfm
Air Inlet: 1/4"





GRINDER



SI-2001S-6

Shank Size: 6 mm
Free Speed: 25,000 rpm
Output: 173 w
Weight: 0.37 kg
Avg. Air Consumption: 2.7 cfm
Air Inlet: ¼”



SI-2022S-6

Shank Size: 6 mm
Free Speed: 22,000 rpm
Output: 537 w
Weight: 1.34 kg
Avg. Air Consumption: 4.5 cfm
Air Inlet: ¼”



SI-2500

Disc Size: 100 mm
Spindle Size: M10 x 1.5
Free Speed: 10,000 rpm
Output: 443 w
Weight: 1.87 kg
Avg. Air Consumption: 2.4 cfm
Air Inlet: ¼”



SI-2500L

Disc Size: 100 mm
Spindle Size: M10 x 1.5
Free Speed: 9,000 rpm
Output: 443 w
Weight: 1.82 kg
Avg. Air Consumption: 2.7 cfm
Air Inlet: ¼”

POLISHER



SI-2400

Buff Pad Size: 180 mm
Spindle Size Male: 5/8-11UNC
Free Speed: 2,000 rpm
Output: 511 w
Weight: 2.24 kg
Avg. Air Consumption: 4.0 cfm
Air Inlet: ¼”



SI-2451

Buff Pad Size: 180 mm
Spindle Size Male: 5/8-11UNC
Free Speed: 2,300 rpm
Output: 482 w
Weight: 2.13 kg
Avg. Air Consumption: 3.9 cfm
Air Inlet: ¼”



SI-2501L

Disc Size: 100 mm
Spindle Size: M10 x 1.5
Free Speed: 11,000 rpm
Output: 303 w
Weight: 1.04 kg
Avg. Air Consumption: 2.7 cfm
Air Inlet: ¼”



SI-2600L

Disc Size: 180 mm
Spindle Size: M10 x 1.5
Free Speed: 7,000 rpm
Output: 754 w
Weight: 3.24 kg
Avg. Air Consumption: 4.0 cfm
Air Inlet: ¼”

DRILL



SI-2015AD

Chuck Size: 10 mm
Free Speed: 6,000 rpm
Drilling Cap: 6 mm
Output: 457 w
Weight: 1.06 kg
Avg. Air Consumption: 4.2 cfm
Air Inlet: ¼”



SI-5100A

Chuck Size: 10 mm
Free Speed: 5,000 rpm
Drilling Cap: 6 mm
Output: 390 w
Weight: 0.90 kg
Avg. Air Consumption: 3.3 cfm
Air Inlet: ¼”



SI-5305A

Chuck Size: 10 mm
Free Speed: 2,000 rpm
Drilling Cap: 10 mm
Output: 326 w
Weight: 1.02 kg
Avg. Air Consumption: 3.9 cfm
Air Inlet: ¼”



SI-5305-8A

Chuck Size: 13 mm
Free Speed: 800 rpm
Drilling Cap: 13 mm
Output: 326 w
Weight: 1.45 kg
Avg. Air Consumption: 4.2 cfm
Air Inlet: ¼”





SANDER




SI-2026

Pad Size: 125 mm
Spindle Size: M10 x 1.5
Free Speed: 5,000 rpm
Output: 491 w
Weight: 1.50 kg
Avg. Air Consumption: 4.4 cfm
Air Inlet: 1/4"



SI-2700

Belt Size: 10 x 330 mm
Free Speed: 15,000 rpm
Output: 317 w
Weight: 0.82 kg
Avg. Air Consumption: 3.3 cfm
Air Inlet: 1/4"



SI-2800


Belt Size: 20 x 520 mm
Free Speed: 15,000 rpm
Output: 429 w
Weight: 1.43 kg
Avg. Air Consumption: 3.8 cfm
Air Inlet: 1/4"



SI-2830

Belt Size: 30 x 540 mm
Free Speed: 10,000 rpm
Output: 582 w
Weight: 2.02 kg
Avg. Air Consumption: 5.3 cfm
Air Inlet: 1/4"

AIR SAW & FILE



SI-4710

File Shank Opening: 5 mm
Cutting Cap: 3 mm
Free Speed: 10,000 rpm
Weight: 0.80 kg
Avg. Air Consumption: 1.0 cfm
Air Inlet: 1/4"



SI-3003

Pad Size: 75 x 100 mm
Orbit Dia.: 4 mm
Free Speed: 8,000 rpm
Output: 134 w
Weight: 1.05 kg
Avg. Air Consumption: 2.8 cfm
Air Inlet: 1/4"



SI-3100

Disc Size: 6"
Orbit Dia.: 7 mm
Free Speed: 8,000 rpm
Output: 542 w
Weight: 1.82 kg
Avg. Air Consumption: 2.3 cfm
Air Inlet: 1/4"



SI-3111 / SI-3111-6

Disc Size: 5" or 6"
Orbit Dia.: 5 mm
Free Speed: 9,500 rpm
Output: 148 w
Weight: 1.27 kg
Avg. Air Consumption: 2.3 cfm
Air Inlet: 1/4"

AIR HAMMER



SI-4120A

Shank Size: 10.2 mm
Max. Stroke Length: 10 mm
Free Blow Speed: 2,600 spm
Weight: 1.60 kg
Avg. Air Consumption: 3.0 cfm
Air Inlet: 1/4"



SI-3007

Pad Size: 95 x 175 mm
Orbit Dia.: 4.8 mm
Free Speed: 7,500 rpm
Output: 275 w
Weight: 1.82 kg
Avg. Air Consumption: 2.8 cfm
Air Inlet: 1/4"



SI-3101

Disc Size: 5"
Orbit Dia.: 5 mm
Free Speed: 10,000 rpm
Output: 148 w
Weight: 0.92 kg
Avg. Air Consumption: 2.2 cfm
Air Inlet: 1/4"



SI-3101-6

Disc Size: 6"
Orbit Dia.: 5 mm
Free Speed: 10,000 rpm
Output: 148 w
Weight: 0.92 kg
Avg. Air Consumption: 2.2 cfm
Air Inlet: 1/4"

